

AirGENIO CONTROL SYSTEM




AirGENIO control system


2W AirGENIO control system ensures easy and smart operation of 2W devices. It is full of smart features, which operate the device with a clear focus on minimizing energy consumption and providing maximum comfort to the interior. Each client has a different demand for the technical level of control therefore AirGENIO control provides various solutions from high-tech to basic level, allowing the client to customize their controls to deliver the temperature and ventilation they desire. In addition, the control panel with its colour touch-screen display is an integral part of the system.

Intelligent • Intuitive • Innovative

2W AirGENIO control system



AirGENIO control system




Three levels of AirGENIO control

- 1 AirGENIO Superior** for ventilation & heating
Designed for **sophisticated** technical solutions loaded with excellent functionalities that fulfil all types of ventilation and heating requirements including connectivity to BMS, service software or mobile application.
- 2 AirGENIO Comfort** for ventilation & heating
Control system ideal for **standard** technical solutions where wide range of functionalities is insisted on but slight compromises accepted.
- 3 AirGENIO Basic** for heating only
Mechanical control system with essential functionalities fully covering **basic** technical demands.

AirGENIO control system SOLUTIONS

AirGENIO control provides various solutions from high-tech to basic level allowing the client to customize their controls. Thanks to one platform of the control system you will intuitively know how to set it up and control it.



**AirGENIO
BASIC**



**AirGENIO
COMFORT**



**AirGENIO
SUPERIOR**



**AirGENIO
IC-C**

Control panel	Manual	Touch-screen	Touch-screen	Touch-screen
Mode	Manual	Auto / Manual	Auto / Manual	Auto / Manual
Fan control	3 speeds (AC) 15-100% (EC)	3 speeds (AC) 15-100% (EC)	3 speeds (AC) 15-100% (EC)	5 speeds (AC) 15-100% (EC)
Electric heater control	2 steps	2 steps	Fluent (PWM)	Fluent (PWM) or 2 steps
Water heater control	ON/OFF	ON/OFF (AC) 0-10V or ON/OFF (EC)	0-10V	0-10V or ON/OFF
Anti-freeze protection	✗	✓	✓	✓
Timer	✗	✓	✓	✓
Door contact	✓ (230V)	✓ (12V, 230V)	✓ (12V, 230V)	✓ (12V, 230V)
Room thermostat	✓ (230V)	✓	✓	✓
External control	✗	✓	✓	✓
Error contact	✗	✓	✓	✓
Temperature measurement	✗	✓ (NTC)	✓ (NTC)	✓ (NTC)
Chaining	✗	✓ – max 10+1 pcs	✓ – max 10+1 pcs	✓ – max 10+1 pcs
BMS connection	✗	✓ – Modbus RTU	✓ – Modbus RTU/TCP or BACnet	✓ – Modbus RTU/TCP or BACnet
Service Software	✗	✗	✓	✓
Auto-speed control	✗	✓	✓	✓
Self-learning mode	✗	✓	✓	✓
Summer heating	✗	✓	✓	✓
Night mode	✗	✓	✓	✓